

ND CleanMove 4 Battery

Disinfection – Without chemicals

UVC Disinfection

ND CleanMove 4 - battery is a portable UV unit that is used for surface and air disinfection in laboratories, meeting rooms and all areas where flexible disinfection is desired. ND CleanMove 4 - battery inactivates up to 99,99% of bacteria, fungi and viruses in the illuminated area.

ND CleanMove 4 - battery:

- → Flexible solution
- → Moveable unit
- → Standalone unit
- → Proven technology with high UVC performance
- → High efficiency with up to 99,99% inactivation
- → Compact solution designed for high status environments.



Used in:

- → Offices
- → Meeting rooms
- → Common areas
- → Canteens
- → Food production rooms
- → Industry



NATDIS | BRUNBJERG 70 | 6100 HADERSLEV | +45 22 680 680 | MAIL@NATDIS.DK | CVR: DK21586544 | NATDIS.EU

Responsible: SPS Version date: 23.01.2025 File no.: ND-DB.uk.FlytbareE.2
Approver: Revision no.: 2 Page 1 af 2



ND CleanMove 4 Battery

Disinfection – Without chemicals

→ Pharmaceutical industry

Read more about UVC here.

Technical information:

UV unit for surface and air disinfection. CleanMove 4 – battery is a battery powered mobile module on wheels that can be easily transported around for disinfection of air and surfaces. The disinfection rate is up to 99,99% on a wide range of bacteria, viruses and fungi on all illuminated surfaces. The unit has a processing radius of 5 meters with a processing time of approx. 13.61 min (depending on selected UVC dose).

The unit has built-in electronics in the bottom module. The unit is available with remote control for dedicated control box or control box connected by cable.

Specifications Specification may vary based on individual configurations	
Product name	ND CleanMove 4 - battery
Lifetime on the bulb	Up to 10.000 hours or 3000 On/Off or 2 years from delivery
Ambient temperature	20-40°C
Number of UVC lamps	4 pcs.
UVC dose*	940 μW/cm²
IP	54
Electric info	230V – 4×90W
${\sf Height} \times {\sf Length} \times {\sf Bredde}$	
Weight	50 kg
Material	Aluminium
Protection against glass shattering	Optional coating of Food contact material approved FEP

^{*} The UVC dose is measured at a distance of 100 cm according to the norm and with the use of an approved ballast.

NATDIS | BRUNBJERG 70 | 6100 HADERSLEV | +45 22 680 680 | MAIL@NATDIS.DK | CVR: DK21586544 | NATDIS.EU

Responsible: SPS Version date: 23.01.2025 File no.: ND-DB.uk.FlytbareE.2
Approver: Revision no.: 2 Page **2** af **2**