

ND CleanMove 1 Hygiene

Disinfection – Without chemicals

UVC Disinfection

ND CleanMove 1 Hygiene is a portable UV unit that is used for surface and air disinfection in rooms from laboratories, to meeting rooms, to high status rooms. ND CleanMove 1 Hygiene inactivates up to 99,99% of bacteria, fungi and viruses in the illuminated area.

ND CleanMove 1 Hygiene:

- → Flexible solution
- → Moveable unit
- → Standalone unit
- → Proven technology with high UVC performance
- → High efficiency with up to 99,99% inactivation
- → Compact solution designed for high status environments.



Used in:

- → Offices
- → Common rooms
- → Hospitals
- Cleanroom environments
- → Food production rooms
- → Industry
- Pharmaceutical industry



Read more about UVC here

Technical information:

ND CleanMove 1 Hygiene is a moveable UVC unit that can be used as a single unit or connected in series. It is connected with a 230V cable and comes with intelligent control that ensures optimal function and is user friendly.

It is designed for use in clean room environments and meets requirements for class A & B rooms in the pharmaceutical industry.

Responsible: SPS Version date: 19.11.2025 File no.: ND-DB.uk.FlytbareE.4
Approver: DVP Revision no.: 3 Page 1 af 2



ND CleanMove 1 Hygiene

Disinfection - Without chemicals

The disinfection rate is up to 99,99% on a wide range of bacteria, viruses and fungi on all illuminated surfaces. The unit has a processing radius of up to 10 meters and is supplied with a standard program and PLC control.

Specifications Specification may vary based on individual configurations	
Product name	ND CleanMove 1 Hygiene
Lifetime on the bulb	Up to 16.000 hours or 3000 On/Off or 2 years from delivery
Ambient temperature	20-40°C
Number of UVC lamps	1 pcs.
UVC dose*	1880 μW/cm²
IP	54
Electric info	230V – (250-400) W
Height × Length × Width	1650mm × 317mm × 317mm
Weight	
Materials	Stainless steel 316 polished or electropolished
Hygienic design	Approved for class A & B
Protection against glass shattering	Optional coating of Food contact material approved FEP
Safety	Active safety is built-in Acoustic and visual alarm warns before start-up. PIR sensor secures persons up to 7 meters away.
Standard programs	Standard programs located in push buttons. 1 button for 5 min 1 button for 10 min 1 button for 15 min 1 button for 20 min

^{*} The UVC dose is measured at a distance of 100 cm according to the norm and with the use of an approved ballast.

Responsible: SPS Version date: 19.11.2025 File no.: ND-DB.uk.FlytbareE.4
Approver: DVP Revision no.: 3 Page 2 af 2